

# 150W Power Supply S-150-48

## Features:

- 48V DC 3.1A output
- AC input voltage range: 92~132V/180~264VAC
- 115V/230V AC selected by switch
- High efficiency low cost
- Free air cooling convection
- Low output ripple and yawp
- Over current, over voltage, short circuit and overheat protections
- 200\*110\*50mm (L\*W\*H)



## General Specification:

|  |                                      |
|--|--------------------------------------|
| <b>Model</b>                           | <b>S-150-48</b>                      |
| <b>DC Output</b>                       | 48V 3.1A                             |
| <b>Wave and Noise</b>                  | 240mVp-p                             |
| <b>Inlet Stability</b>                 | ±0.2%                                |
| <b>Load Stability</b>                  | ±0.2%                                |
| <b>Efficiency</b>                      | 87%                                  |
| <b>Adjustable range for DC Voltage</b> | 42.5V~52V                            |
| <b>AC Input Voltage</b>                | 92~132V/180~264VAC Slected by Switch |
| <b>AC Input Current</b>                | 3.2A/115VAC 1.6A/230VAC              |
| <b>Working Temperature</b>             | -10~50°C                             |
| <b>Safety Standards</b>                | GB4943, UL60950, EN60950             |
| <b>EMC Standards</b>                   | GB9254, 55022, ClassB                |
| <b>Weight</b>                          | 0.85kg                               |

## Dimensions:

